


Chain Types: C0880T, C0879T, C1061T, C0881T & C8811T. Also compatible: C0890T & C0770T Chain width: 3.25"/3.30",4.50",7.50" **Standard materials:** U - PE40-W (Nat. White) R - PE10-B (Black) Other materials on request: TP40-C (Blue) PE05B (Black) Lanes: 1, Additional lanes on request. Supplied as: Single lane. For carry + return, order 2 lines.





## Data

Chain width	Lanes	Width W	Length 2 m	Length 10 ft
3.25/3.30"	1	100	SE160TT200-1#-00	SE160TT305-1#-00
4.50"	1	130	SE230TT200-1#-00	SE230TT305-1#-00
7.50"	1	200	SE380TT200-1#-00	SE380TT305-1#-00

Complete the product code by substituting # with the chosen material code Ex.: SE160TT200-1U-00 (straight track in PE40-W)

## Disclaimer

## Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

Product Application Disclaimer (valid of ALL mapsit products and mentioned on all PDS) This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to to assessments and modifications within a short portion of time and without refer partice.

at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice. EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.