

# Cleandrive Postitive Drive Belts

## CD.P25-A-UC+TS



### Main industry segments



Bread, Candy, Chocolate, Dairy (incl. cheese), Frozen food, Fruit, Pizza, Poultry, Ready meals, Red meat, Seafood, Vegetables

### Applications

Food processing/conveying belt

### Special features

Abrasion resistant on both sides, Bi-directional suitable, Easy cleanability, Easy release



| Product Construction / Design |                                  |
|-------------------------------|----------------------------------|
| Material                      | Thermoplastic polyurethane (TPU) |
| Color                         | Cobalt blue                      |
| Conveying side surface        | Sawtooth profile structure       |
| Conveying side property       | Medium-adhesive                  |
| Traction layer (material)     | Aramid cords                     |
| Pulley side surface           | Glossy                           |
| Pulley side geometry          | Drive bars                       |

| Product characteristics           |                                                        |
|-----------------------------------|--------------------------------------------------------|
| Antistatically equipped           | No                                                     |
| Slider bed suitable               | Yes                                                    |
| Carrying rollers suitable         | No                                                     |
| UV-C suitable                     | No                                                     |
| Laser markable                    | Yes                                                    |
| Flammability                      | No specific flammability prevention property           |
| Food suitability, EU conformance  | Yes - Check Document of Compliance (DoC) in our Portal |
| Food suitability, FDA conformance | Yes - Check Document of Compliance (DoC) in our Portal |
| Other conformance/approval        | Japanese Food Regulation (MHLW Notification No. 370)   |

# Cleandrive Postitive Drive Belts

## CD.P25-A-UC+TS



| Technical data                                             |      |                   |                |
|------------------------------------------------------------|------|-------------------|----------------|
| Hardness                                                   | 95   | Shore A           |                |
| Thickness of belt                                          | 2.6  | mm                | 0.102 inch     |
| Distance between cords                                     | 15   | mm                | 0.59 inch      |
| Nominal drive bar pitch                                    | 26.8 | mm                | 1.055 inch     |
| Mass of belt (belt weight)                                 | 3.6  | kg/m <sup>2</sup> | -2.000 lb/sqft |
| Min. operating temperature admissible (continuous)         | -20  | °C                | -4 °F          |
| Max. operating temperature admissible (continuous)         | 80   | °C                | 176 °F         |
| Coefficient of friction (pulley side / PE sliding support) | 0.40 | -                 |                |
| Minimal width of belt                                      | 150  | mm                | 6 inch         |
| Seamless manufacturing width                               | 609  | mm                | 23.98 inch     |

### Joining related properties

| Joining method            |                                                 |
|---------------------------|-------------------------------------------------|
| Quickmelt                 | Master joining method for standard applications |
| Mechanical Lace (SS Rod)  | Optional joining method                         |
| Mechanical Lace (POM Rod) | Optional joining method                         |

[Link to JDS:](#)

| Joining method                                                      |                | Quickmelt    | Mechanical Lace (SS Rod) | Mechanical Lace (POM Rod) |
|---------------------------------------------------------------------|----------------|--------------|--------------------------|---------------------------|
| Minimal pitch diameter for driving sprockets                        | mm<br>inch     | 60.1<br>2.37 | 60.1<br>2.37             | 60.1<br>2.37              |
| Minimal pitch diameter for idling sprockets                         | mm<br>inch     | 43.0<br>1.69 | 43.0<br>1.69             | 43.0<br>1.69              |
| Minimal back-bending roller diameter for center drive configuration | mm<br>inch     | 75<br>3      | 75<br>3                  | 75<br>3                   |
| Minimal diameter for belt support roller                            | mm<br>inch     | 50<br>2      | 50<br>2                  | 50<br>2                   |
| Admissible tensile force per unit of width                          | N/mm<br>lbf/in | 6.0<br>34    | 3.0<br>17                | 1.8<br>10                 |
| Troughed installation suitable                                      |                | Yes          | No                       | No                        |
| X-Ray / Metal detectable material                                   |                | No           | No                       | No                        |
| X-Ray / Metal detector suitable                                     |                | Yes          | No                       | Yes                       |

*All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554). Limited representative testing based on a standard configuration is carried out to estimate minimum pulley diameters. Please contact Habasit for specific guidance regarding non-standard applications, including, but not exclusively, when profiles or cleats are used, or if the belt working temperature is close to the limits listed in this document.*

### Chemical resistance

Link to 'Chemical resistance information': <https://rims.habasit.com>

### Calculations

Please ask your local Habasit partner to calculate your needs for you and receive the best advise specially suited for your application.

# Cleandrive Postitive Drive Belts

## CD.P25-A-UC+TS



### Recommendation

See Engineering Manual

Store spare belts in a cool and dry place and if possible in their original packaging. Protect spare belts from sunlight/UV-radiation/dust/dirt! Check Link for Storage requirements:

["https://tdm.habasit.com/pds/en-us/Storage%20of%20Habasit%20material.pdf"](https://tdm.habasit.com/pds/en-us/Storage%20of%20Habasit%20material.pdf)

This product has not been tested according to ATEX standards (atmospheres with explosion risk - ATEX 95 regulation or EU directive 2014/34/EU) and therefore is subject to user's analysis in the respective environment



**Sprockets**

Habasit® Cleandrive series

**Sprockets**

Habasit® Cleandrive HyCLEAN series

**Profiles**

Longitudinal and transversal profiles

Group

Cleandrive Positive Drive

Cleandrive Belt Series CD25

Item number

H950042484

### Disclaimer

#### Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice. EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.