


Hygienic Cleats E-PH-F



Main applications

Habasit Hygienic Cleats represent a set of TPU and PVC flights specifically designed for Food Industry in order to meet the higher standards of hygiene and cleanability for a fabricated conveyor belt. They can be used with good results in all applications where cleanliness, hygiene and small pulley diameters are critical factors and they are the best solution for the food processing industries, such us: Agriculture, Bakery, Confectionery and Chocolate, Meat and Poultry.



Description

Key features of Habasit Hygienic Cleats are: Improved foot design in comparison with current PT and PN existing profiles, that allow to have less contamination areas; Cleaning of fabricated belt with flights easier; Smaller pulley diameters: increased profile flexibility.

Product data

Technical data	
Material type	TPU Polyester
Hardness	85 ShA

Code	Item number	Color	Food grade	DoC Name	Width mm	Height mm	Package	Quantity	Units	Box Content	Weight kg
E-PH40-FC-B72	H950027988	Cobalt blue	Yes	FC	19.2	40.0	Box	72	M	30 bars	0.4
E-PH40-FW-B72	H950027989	White	Yes	FW	19.2	40.0	Box	72	M	30 bars	0.4
E-PH60-FC-B43	H950027990	Cobalt blue	Yes	FC	19.2	60.0	Box	43	M	18 bars	0.6
E-PH60-FW-B43	H950027991	White	Yes	FW	19.2	60.0	Box	43	M	18 bars	0.6
E-PH80-FC-B36	H950027992	Cobalt blue	Yes	FC	19.2	80.0	Box	36	M	15 bars	0.8
E-PH80-FW-B36	H950027993	White	Yes	FW	19.2	80.0	Box	36	M	15 bars	0.8

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554). Limited representative testing based on a standard configuration is carried out to estimate minimum pulley diameters. Please contact Habasit for specific guidance regarding non-standard applications, including, but not exclusively, when profiles or cleats are used, or if the belt working temperature is close to the limits listed in this document.

Code	Minimum pulley dia. conveying side transversal mm
E-PH40-FC-B72	80
E-PH40-FW-B72	80
E-PH60-FC-B43	80
E-PH60-FW-B43	80
E-PH80-FC-B36	80
E-PH80-FW-B36	80

Chemical resistance

Link to 'Chemical resistance information': <https://rims.habasit.com>

Recommendation

General dimensional tolerance: $\pm 3\%$ or ± 0.20 mm (whichever is greater).

Disclaimer

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.