



Product data

Technical data					
Material type	TPU Polyether				
Hardness	83	ShA			

Code	Item number	Color	Food grade	DoC Name	В	b	h	Weight
					mm	mm	mm	kg/m
E-PV17-GC-C50	H950028024	Cobalt blue	Yes	GC	17	10.0	11.4	0.18
E-PV06-GC-C300	H090035180	Cobalt blue	Yes	GC	6	4.0	3.9	0.02
E-PV06-GW-C300	H090035182	White	Yes	GW	6	4.0	3.9	0.02
E-PV08-GC-C200	H090035181	Cobalt blue	Yes	GC	8	5.5	5.2	0.04
E-PV08-GW-C200	H090035185	White	Yes	GW	8	5.5	5.2	0.04
E-PV10-GC-C200	H090035179	Cobalt blue	Yes	GC	10	6.0	6.4	0.06
E-PV10-GW-C200	H090035183	White	Yes	GW	10	6.0	6.4	0.06
E-PV13-GC-C100	H090035174	Cobalt blue	Yes	GC	13	7.5	8.4	0.09
E-PV13-GW-C100	H090035184	White	Yes	GW	13	7.5	8.4	0.09

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554).

Code	Minimum pulley dia. conveying side transversal	Minimum pulley dia. conveying side longitudinal	Minimum pulley diameter running side	
	mm	mm	mm	
E-PV17-GC-C50	120	160	110	
E-PV06-GC-C300	60	50	40	
E-PV06-GW-C300	60	50	40	
E-PV08-GC-C200	70	80	50	
E-PV08-GW-C200	70	80	50	
E-PV10-GC-C200	90	110	60	
E-PV10-GW-C200	90	110	60	
E-PV13-GC-C100	120	140	80	
E-PV13-GW-C100	120	140	80	

Chemical resistance

Link to 'Chemical resistance information': https://rims.habasit.com

Recommendation

General dimensional tolerance: ±3% or ±0.20 mm (whichever is greater).



Disclaimer

Disclaimer Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS) This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice. EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.