

### CJ-T5 Joining Plate

Fixed width toothed plate with T5 pitch inclusive a covering plate.



Technical data		
Max Belt Thickness	2 mm	0.09 inch
Custom Tariff	85159080	

Available versions	Item number
CJ-T5-100-03	H088000007
CJ-T5-10-03	H088000105
CJ-T5-125-03	H088000008
CJ-T5-150-03	H088000009
CJ-T5-16-03	H088000002
CJ-T5-25-03	H088000003
CJ-T5-32-03	H088000004
CJ-T5-50-03	H088000005
CJ-T5-75-03	H088000006

Available versions	Length	Width	Height	Weight
CJ-T5-100-03	340 mm ( 13.386 inch )	116.5 mm ( 4.587 inch )	15.5 mm ( 0.610 inch )	5 kg ( 10.1 lb )
CJ-T5-10-03	340 mm ( 13.386 inch )	26.3 mm ( 1.035 inch )	15.5 mm ( 0.610 inch )	1.0 kg ( 2.2 lb )
CJ-T5-125-03	340 mm ( 13.386 inch )	141.8 mm ( 5.583 inch )	15.5 mm ( 0.610 inch )	6 kg ( 12.3 lb )
CJ-T5-150-03	340 mm ( 13.386 inch )	166.8 mm ( 6.567 inch )	15.5 mm ( 0.610 inch )	7 kg ( 14.3 lb )
CJ-T5-16-03	340 mm ( 13.386 inch )	32.3 mm ( 1.272 inch )	15.5 mm ( 0.610 inch )	1.2 kg ( 2.6 lb )
CJ-T5-25-03	340 mm ( 13.386 inch )	41.3 mm ( 1.626 inch )	15.5 mm ( 0.610 inch )	1.6 kg ( 3.5 lb )
CJ-T5-32-03	340 mm ( 13.386 inch )	48.3 mm ( 1.902 inch )	15.5 mm ( 0.610 inch )	2 kg ( 4.0 lb )
CJ-T5-50-03	340 mm ( 13.386 inch )	66.5 mm ( 2.618 inch )	15.5 mm ( 0.610 inch )	3 kg ( 5.5 lb )
CJ-T5-75-03	340 mm ( 13.386 inch )	91.5 mm ( 3.602 inch )	15.5 mm ( 0.610 inch )	4 kg ( 7.9 lb )

#### Disclaimer

#### Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.