

### PF-150CW Press stand for PF-150C Hot pressing device

The PF-150CW press stand has been designed to house the PF-150C and to support the mass fabrication of timing belts. A two hands pneumatic control activates an air cylinder that closes/opens the press and applies the needed pressure for the joining cycle. The pressure level is adjustable by a handgrip and by a gauge installed on the front panel. The lower plate can be tilted in order to allow the joining of short belts.



Adjustable Temperature	Adjustable by control unit		
Cooling Media	Water (ext. supply)		
Max Belt Thickness	11 mm	0.43 inch	
Belt/tape width max.	152 mm	6 inch	
Pneumatics Operating Pressure	6 bar		
Custom Tariff	84798997		

Available versions	Item number	Power supply	Control unit	Cooling unit
PF-150C-W-AFP/8	H088000470	1ph 230V 50Hz	PMR-08	PFC-07
PF-150C-W-CFP/6	H088000116	1ph 120V 60Hz	PMR-07	PFC-07
PF-150C-W-CFP/8	H088000115	1ph 230V 50Hz	PMR-07	PFC-07

Available versions	Length	Width	Height	Weight	Operating temperature max
PF-150C-W-AFP/8	510 mm ( 20.079 inch )	350.0 mm ( 13.780 inch )	180.0 mm ( 7.087 inch )	114 kg ( 251.3 lb )	200 °C ( )
PF-150C-W-CFP/6	510 mm ( 20.079 inch )	350.0 mm ( 13.780 inch )	180.0 mm ( 7.087 inch )	114 kg ( 251.3 lb )	200 °C ( )
PF-150C-W-CFP/8	510 mm ( 20.079 inch )	350.0 mm ( 13.780 inch )	180.0 mm ( 7.087 inch )	114 kg ( 251.3 lb )	200 °C ( )

#### Disclaimer

#### Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice. EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.