

PT-100 Hot pressing device

The PT-100 is a hot-pressing device for Thermofix joining of Habasit belts and tapes up to a width of 100 mm and a thickness of 6 mm. The lower press plate is heated and is equipped with a detachable set-up plate with clamping springs for secure positioning of the belt ends. Its knuckle joint mechanism allows easy adjustment for different belt thicknesses. Together with the integrated pressure equalization pad, it ensures reliable hot pressing for even the most demanding glued belt joints. The PT-100 hot-pressing device is equally well suited for workshop use and on-site installations.



Adjustable Temperature	No
Cooling Media	Ambient air
Max Belt Thickness	6 mm 0.24 inch
Belt/tape width max. for joining angle of 60°	45 mm
Belt/tape width max. For joining angle of 75°	75 mm
Belt/tape width max.	100 mm 4 inch
Custom Tariff	85158090

Available versions	Item number	Power supply
PT-100/6	H080690070	1ph 120V 60Hz
PT-100/8	H080690090	1ph 230V 50Hz

Available versions	Length	Width	Height	Weight
PT-100/6	285 mm (11.220 inch)	128.0 mm (5.039 inch)	102.0 mm (4.016 inch)	2 kg (4.4 lb)
PT-100/8	285 mm (11.220 inch)	128.0 mm (5.039 inch)	102.0 mm (4.016 inch)	2 kg (4.4 lb)

Disclaimer

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice. EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.