



# HabasitLINK® M2483 Sphere Top 1"



## Description

- Designed for multi-directional product handling
- Imperial belt width
- Closed hinge
- Floater diameter 3 mm (0.12")
- Lug teeth sprockets
- Admissible load per sphere 0.5 kg (1.10 lb)



## Belt data

Belt material		POM
Rod material		PA
Roller material		PA
Nominal tensile strength $F'_N$ straight run	N/m lb/ft	25000 1712
Temperature range	°C °F	10 - 30 50 - 86
Belt weight $m_B$	kg/m <sup>2</sup> lb/sqft	9.6 1.97

**Note:** Temperature range is valid for belt widths up to 2032 mm (80") for other belt widths and temperatures please contact Habasit.

Diameter of idling rollers (minimum)		Diameter of support rollers (minimum)		Diameter for gravity take-up and center drive rollers (minimum)	
mm	inch	mm	inch	mm	inch
50	2.00	50	2.00	100	4

## Standard range of belt widths $b_0$

mm (nom.)	152	229	305	381	457	533	610	686	762	838	914	991	etc.
inch (nom.)	6	9	12	15	18	21	24	27	30	33	36	39	etc.

Real belt widths are in most cases 0.1% to 0.4% smaller.

**Standard belt widths** in increments of 76.2 mm (3"). Non-standard widths are offered in increments of 25.4 mm (1"). Smallest possible width 76.2 mm (3").

**For detailed material properties** refer to the HabasitLINK® Engineering Guidelines.

**The nominal tensile strength** is valid for 23 °C (73 °F). The admissible tensile force depends on the operating temperature near the drive sprockets. Within the temperature range allowed, the admissible tensile force may vary from 100% to 20% of the nominal tensile strength. For detailed information and correct calculation of effective tensile force refer to the Calculation Guide in the HabasitLINK® Engineering Guidelines.

# HabasitLINK®

## M2483 Sphere Top 1"



### **Disclaimer**

#### **Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)**

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.