

Bent Tip Cleats E-PB-G




Main applications

Transversally applied on the belt, the profile assists secure product movement in steep inclined and declined applications. Mainly used in the food processing industry and for bulk material transport in general.

Description

Narrow-based cranked T-profile used as a cleat on TPU conveyor and processing belts.

Profiles are applied to the belt surface using high frequency welding procedure. Suitable for TPU Premium fabric belts.



Product data

Technical data											
Material type					TPU Polyether						
Hardness					83 ShA						
Code	Item number	Color	Food grade	DoC Name	Width	Height	Package	Quantity	Units	Box Content	Weight
					mm	mm					kg
E-PB20-GC-B120	H950022343	Cobalt blue	Yes	GC	12	20	Box	120.0	M	50 bars	0.090
E-PB20-GW-B120	H950022353	White	Yes	GW	12	20	Box	120.0	M	50 bars	0.090
E-PB30-GC-B84	H950022344	Cobalt blue	Yes	GC	12	30	Box	84.0	M	35 bars	0.127
E-PB30-GW-B84	H950022354	White	Yes	GW	12	30	Box	84.0	M	35 bars	0.127
E-PB40-GC-B60	H950022345	Cobalt blue	Yes	GC	12	40	Box	60.0	M	25 bars	0.171
E-PB40-GW-B60	H950022355	White	Yes	GW	12	40	Box	60.0	M	25 bars	0.171
E-PB50-GC-B48	H950022346	Cobalt blue	Yes	GC	12	50	Box	48.0	M	20 bars	0.215
E-PB50-GW-B48	H950022356	White	Yes	GW	12	50	Box	48.0	M	20 bars	0.215

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554).

Chemical resistance

Link to 'Chemical resistance information': <http://www.habasit.com/en/chemical-resistance.htm>

Recommendation

General dimensional tolerance: $\pm 3\%$ or ± 0.20 mm (whichever is greater).

Disclaimer

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice. EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.