
HabaSYNC® Timing Belts Covers
N Rubber White



Product Construction / Design	
Material	Natural rubber (NR)

Technical data		
Min. operating temperature admissible (continuous)	-40 °C	*-40 °F*
Max. operating temperature admissible (continuous)	75 °C	*167 °F*

Product code	Thickness		Hardness	Color	Conveying side surface	Conveying side property	Thickness factor	Food grade[1]
	mm	*inch*	Shore A					DoC
AC-N-RUBBER WHITE 2MM	2.0	*0.08*	38	Off-white	Smooth	Super-adhesive	20	AC-N-Rubber White
AC-N-RUBBER WHITE 3MM	3.0	*0.12*	38	Off-white	Smooth	Super-adhesive	20	AC-N-Rubber White
AC-N-RUBBER WHITE 4MM	4.0	*0.16*	38	Off-white	Smooth	Super-adhesive	20	AC-N-Rubber White
AC-N-RUBBER WHITE 5MM	5.0	*0.20*	38	Off-white	Smooth	Super-adhesive	20	AC-N-Rubber White
AC-N-RUBBER WHITE 6MM	6.0	*0.24*	38	Off-white	Smooth	Super-adhesive	20	AC-N-Rubber White

[1] This product is in compliance with relevant EU and/or US food contact requirements. Check the following link for detailed information **Documents of Compliance**

Hardness and thickness are statistical values and may vary slightly between different production lots.

The recommended minimum pulley diameter is determined by multiplying the cover thickness by the thickness factor. For design purposes, always use the larger suggested diameter between the belt and the selected cover.

Limited representative testing, based on a standard configuration, is conducted to estimate minimum pulley diameters. Please contact Habasit for specific guidance regarding non-standard applications, including, but not limited to, cases where special customizations are in place, such as profiles or cleats, or when holes, pockets, countersinks, sipes, or similar machining processes are applied.

Not all covers may be available in your local market. Please consult your local Habasit representative.

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554).

HabaSYNC® Timing Belts Covers
N Rubber White

Chemical resistance
Link to 'Chemical resistance information': https://rims.habasit.com

Group	HabaSYNC® Timing Belts Covers Elastomer Covers

Disclaimer
Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)
This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.
EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.