



產品架構/設計	
材料	天然橡胶 (NR)

技术数据		
最低允许允许温度(连续)	-40 °C	-40 °F
最高允许允许温度(连续)	70 °C	158 °F

Product code	厚度		硬度	颜色	输送面 (表面)	输送面 (特性)	厚度系数	食品适用 ¹
	毫米	英寸						
AC-LINATEXHM-2MM	2.0	0.08	40	红色	光滑	超强黏性	20	-
AC-LINATEXHM-3MM	3.0	0.12	40	红色	光滑	超强黏性	20	-
AC-LINATEXHM-4MM	4.0	0.16	40	红色	光滑	超强黏性	20	-
AC-LINATEXHM-5MM	5.0	0.20	40	红色	光滑	超强黏性	20	-
AC-LINATEXHM-6MM	6.0	0.24	40	红色	光滑	超强黏性	20	-
AC-LINATEXHM-8MM	8.0	0.31	40	红色	光滑	超强黏性	20	-

Hardness and *Thickness* are statistical values which may vary slightly in between different production lots.

Recommended minimum pulley diameter is the result of multiplying the cover *Thickness* by the *Thickness factor*. For design purposes, always use the larger suggested diameter of the belt and cover selected.

Limited representative testing based on a standard configuration is carried out to estimate minimum pulley diameters. Please contact Habasit for specific guidance regarding non-standard applications, including, but not exclusively, when profiles or cleats are used.

All covers may not be available in your local market. Please consult your local Habasit representative.

所有数据均为标准气候条件下的近似值: 23°C/73°F, 50% 相对湿度 (DIN 50005/ISO 554).

