Flat Belts for Cleat Applications F-PF-H



Main applications

Transversally applied on the belt, the profile assists secure product movement in inclined and declined applications. Mainly used in the food processing industry and for bulk material transport in general.

Description

Thicker extruded food-grade flat belt used as a cleat.



Product data

Technical data		
材質類型	TPU Polyether	
Hardness	87 Shore A	

Code	項目編號	顏色	Food grade	DoC Name	Width		Height		重量	
					mm	inch	mm	inch	kg/m	lbs/ft
E-PF60-HC-B010	H950045812	鈷藍	是	HC	6.0	0.236	240.0	9.449	1.61	1.08
E-PF60-HW-B010	H950046148	白色	是	HW	6.0	0.236	240.0	9.449	1.61	1.08
E-PF80-HC-B006	H950045813	鈷藍	是	HC	8.0	0.315	240.0	9.449	2.15	1.44
E-PF100-HC-B006	H950045863	鈷藍	是	HC	10.0	0.394	240.0	9.449	2.69	1.81

所有数据均为标准气候条件下的粗略值: 23°C/73°F, 相对湿度50% (DIN 50005/ISO 554), 并基于主要接著方式。

Limited representative testing based on a standard configuration is carried out to estimate minimum pulley diameters. Please contact Habasit for specific guidance regarding non-standard applications, including, but not exclusively, when profiles or cleats are used, or if the belt working temperature is close to the limits listed in this document.

抗化學特性

关于"抗化学性信息"的网页: https://rims.habasit.com

介绍

General dimensional tolerance: ±3% or ±0.20 mm (whichever is greater).