

HabasitLINK® Accessories – 2" Pitch Belting Flights and Sideguards M5000

Compatibility of 2" flights and belt types

In general all 2" flights may be used in combination with all 2" belts. For some combinations the nominal tensile strengths of the belt will be reduced to the strength of the flight.

Please see the table below.

Flights and Sideguards M5000 Series (except M5060)

	Flight	M5010Fxx, M5010Bxx M5010Pxx, M5014F10			M5033Fxx			M5015Fxx			
	Belt material	PP	POM		PP	POM		PP		POM	
	Rod material	PP/POM	PP	PA	PP/POM	PP/POM	PA	PP	POM	PP	PA
Nominal tensile strength N/m lb/ft	M5010	18'000	22'000	30'000	18'000	22'000	30'000	18'000	18'000	22'000	30'000
	M5011	1'233	1'507	2'055	1'233	1'507	2'055	1'233	1'233	1'507	2'055
	M5013										
	M5014										
	M5015							29'000 1'986	31'000 2'123	31'000 2'123	53'000 3'630
	M5020	18'000	22'000	30'000	26'000	30'000	35'000	29'000	31'000	31'000	53'000
	M5023	1'233	1'507	2'055	1'781	2'055	2'397	1'986	2'123	2'123	3'630
M5032											
M5033	18'000 1'233							26'000 1'781	26'000 1'781	30'000 2'055	35'000 2'397
M5131 M50xx Roller Top	not applicable										

For M5060 belt types only M5060Fxx flight can be used. A combination with other flight series is not possible.