


### Main applications

Flat belts are monolithic belts to convey goods in different applications or used as sideskirts. As an alternative they can be used as accessories for fabricated belts (i.e. as special cleats or sidewalls) or cover for timing belts.

### Description

Habasit flat belts are produced with smooth or embossed surfaces in TPU, hydrolysis resistant TPU and PVC in different thicknesses from 1.35 mm to 7 mm. Right products have to be selected on the base of the specific application.



### Product data

Technical data	
Material type	TPU Polyester
Hardness	85 ShA

Code	Item number	Color	Food grade	DoC Name	Width	Package	Quantity	Units
					mm			
E-FB13-FC-C100	S090060046	Cobalt blue	Yes	FC	270.0	Coil	27	M2
E-FB13-FG-C100	S090060040	Green	Yes	FG	270.0	Coil	27	M2
E-FB13-FD-C100	S090060042	Dark green	Yes	FD	270.0	Coil	27	M2
E-FB13-FW-C100	S090060041	White	Yes	FW	270.0	Coil	27	M2
E-FB17-FW-C100	H090060096	White	Yes	FW	270.0	Coil	27	M2
E-FB20-FC-C100	H090060079	Cobalt blue	Yes	FC	270.0	Coil	27	M2
E-FB20-FT-C100	H090060134	Transparent	Yes	FT	270.0	Coil	27	M2
E-FB20-FW-C100	H090060047	White	Yes	FW	270.0	Coil	27	M2
E-FB30-FC-C50	H090060080	Cobalt blue	Yes	FC	260.0	Coil	13	M2
E-FB30-FT-C50	H090060102	Transparent	Yes	FT	260.0	Coil	13	M2
E-FB30-FW-C50	H090060097	White	Yes	FW	260.0	Coil	13	M2
E-FB40-FD-C50	H090060129	Dark green	Yes	FD	240.0	Coil	12	M2
E-FB40-FW-C50	H090060048	White	Yes	FW	240.0	Coil	12	M2
E-FB50-FC-C25	H090060098	Cobalt blue	Yes	FC	240.0	Coil	6	M2
E-FB50-FW-C25	H090060049	White	Yes	FW	240.0	Coil	6	M2
E-FB50-FW-C50	H090060128	White	Yes	FW	240.0	Coil	12	M2

*All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554). Limited representative testing based on a standard configuration is carried out to estimate minimum pulley diameters. Please contact Habasit for specific guidance regarding non-standard applications, including, but not exclusively, when profiles or cleats are used, or if the belt working temperature is close to the limits listed in this document.*

### Chemical resistance

Link to 'Chemical resistance information': <https://rims.habasit.com>

### Recommendation

General dimensional tolerance:  $\pm 3\%$  or  $\pm 0.20$  mm (whichever is greater).

### **Disclaimer**

#### **Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)**

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.