

V-Shaped monolithic belts

E-VR-K



Main applications

Habipur V- belts are trapezoidal profiles that are used in linear conveyors especially in ceramic and material handling industries. Available also in the reinforced version (Habipur E-VR), for heavier applications.

Description

Highly flexible V-shaped TPU belts running over pulleys compliant with DIN2215. High abrasion and chemical resistance. Very good weldability.



Product data

Technical data	
Material type	TPU Polyester
Hardness	90 ShA
Temperature correction factor	0.85
Min. operating temperature admissible (continuous)	-20 °C
Max. operating temperature admissible (continuous)	50 °C
Coefficient of friction on steel	0.15

Code	Item number	Color	Food grade	Width	Height	Package	Quantity	Units	Weight
				mm	mm				
				kg					
E-VR13-KC-C100	H090033613	Cobalt blue	No	13.0	8.0	Coil	100	M	0.097
E-VR17-KC-C50	H090033617	Cobalt blue	No	17.0	11.0	Coil	50	M	0.175
E-VR17-KR-C50	S090033619	Red	No	17.0	11.0	Coil	50	M	0.175
E-VR22-KC-C50	H090033622	Cobalt blue	No	22.0	14.0	Coil	50	M	0.285

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554). Limited representative testing based on a standard configuration is carried out to estimate minimum pulley diameters. Please contact Habasit for specific guidance regarding non-standard applications, including, but not exclusively, when profiles or cleats are used, or if the belt working temperature is close to the limits listed in this document.

Code	Nominal peripheral force	Minimum pulley diameter running side
		mm
E-VR13-KC-C100	230	75
E-VR17-KC-C50	320	100
E-VR17-KR-C50		
E-VR22-KC-C50	410	130

Chemical resistance

Link to 'Chemical resistance information': <https://rims.habasit.com>

Recommendation

General dimensional tolerance: $\pm 3\%$ or ± 0.20 mm (whichever is greater).

V-Shaped monolithic belts

E-VR-K



Disclaimer

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.