



Product data

Technical data		
Material type	PVC	
Hardness	65	ShA

Code	Item number	Color	Food grade	DoC Name	B	b	h	Weight
					mm	mm	mm	
E-PV08-RC-C300	H090060117	Cobalt blue	Yes	RC	8	5.5	5.20	0.04
E-PV08-RD-C300	H090060112	Dark green	Yes	RD	8	5.5	5.20	0.04
E-PV08-RW-C300	H090060066	White	Yes	RW	8	5.5	5.20	0.04
E-PV06-RC-C300	H090060116	Cobalt blue	Yes	RC	6	4.0	3.90	0.02
E-PV06-RD-C300	H090060111	Dark green	Yes	RD	6	4.0	3.90	0.02
E-PV06-RW-C300	H090060065	White	Yes	RW	6	4.0	3.90	0.02
E-PV10-RC-C200	H090060118	Cobalt blue	Yes	RC	10	6.0	6.40	0.06
E-PV10-RD-C200	H090060113	Dark green	Yes	RD	10	6.0	6.40	0.06
E-PV10-RW-C200	H090034811	White	Yes	RW	10	6.0	6.40	0.06
E-PV13-RC-C100	H090060119	Cobalt blue	Yes	RC	13	7.5	8.40	0.10
E-PV13-RD-C100	H090060114	Dark green	Yes	RD	13	7.5	8.40	0.10
E-PV13-RW-C100	H090034812	White	Yes	RW	13	7.5	8.40	0.10
E-PV17-RC-C50	H090060120	Cobalt blue	Yes	RC	17	10.0	11.40	0.19
E-PV17-RD-C50	H090060115	Dark green	Yes	RD	17	10.0	11.40	0.19
E-PV17-RW-C50	H090060067	White	Yes	RW	17	10.0	11.40	0.19

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554).

Code	Minimum pulley dia. conveying side transversal	Minimum pulley dia. conveying side longitudinal	Minimum pulley diameter running side
	mm	mm	mm
E-PV08-RC-C300	40	100	50
E-PV08-RD-C300	40	100	50
E-PV08-RW-C300	40	100	50
E-PV06-RC-C300	30	70	40
E-PV06-RD-C300	30	70	40
E-PV06-RW-C300	30	70	40
E-PV10-RC-C200	50	120	60
E-PV10-RD-C200	50	120	60
E-PV10-RW-C200	50	120	60
E-PV13-RC-C100	70	150	80
E-PV13-RD-C100	70	150	80
E-PV13-RW-C100	70	150	80
E-PV17-RC-C50	100	180	120
E-PV17-RD-C50	100	180	120
E-PV17-RW-C50	100	180	120

Chemical resistance

Link to 'Chemical resistance information': <https://rims.habasit.com>

Recommendation

General dimensional tolerance: $\pm 3\%$ or ± 0.20 mm (whichever is greater).

Disclaimer

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice. EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.