

# Tracking guides F-PV-W







### **Product data**

Technical data					
Material type	TPU Polyester				
Hardness	65	ShA			

Code	Item number	Color	Food grade	В	b	h	Weight
				mm	mm	mm	kg/m
E-PV06-WT-C300	H090035150	Transparent	No	6	4.0	3.90	0.02
E-PV10-WT-C200	H090035151	Transparent	No	10	6.0	6.40	0.06
E-PV13-WT-C100	H090035152	Transparent	No	13	7.5	8.40	0.10
E-PV17-WT-C50	H090035153	Transparent	No	17	10.0	11.40	0.17

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554).

Code	Minimum pulley dia. Minimum pulley dia. conveying side transversal conveying side longitudina		Minimum pulley diameter running side	
	mm	mm	mm	
E-PV06-WT-C300	30	40	30	
E-PV10-WT-C200	50	100	50	
E-PV13-WT-C100	80	130	90	
E-PV17-WT-C50	120	150	100	

# **Chemical resistance**

Link to 'Chemical resistance information': https://rims.habasit.com

## Recommendation

General dimensional tolerance: ±3% or ±0.20 mm (whichever is greater).

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.