

Fabrication Tools

GR-PQ-59



GR-PQ-59 Guiderail

Guide rail of fixed width inclusive a covering plate and 2 metal clamps.



Technical data

Custom Tariff

85159080

Available versions	Item number
GR-PQ-59-M-006	H080672006
GR-PQ-59-M-008	H080672008
GR-PQ-59-M-010	H080672010
GR-PQ-59-M-011	H080672011
GR-PQ-59-M-012	H080672012
GR-PQ-59-M-013	H080672013
GR-PQ-59-M-014	H080672014
GR-PQ-59-M-015	H080672015
GR-PQ-59-M-016	H080672016
GR-PQ-59-M-018	H080672018
GR-PQ-59-M-020	H080672020
GR-PQ-59-M-022	H080672022
GR-PQ-59-M-025	H080672025
GR-PQ-59-M-030	H080672030
GR-PQ-59-M-035	H080672035
GR-PQ-59-M-040	H080672040
GR-PQ-59-M-050	H080672050
GR-PQ-59-I-3/8	H080672113
GR-PQ-59-I-1/2	H080672101
GR-PQ-59-I-5/8	H080672114
GR-PQ-59-I-3/4	H080672102
GR-PQ-59-I-7/8	H080672109
GR-PQ-59-I-1	H080672103
GR-PQ-59-I-1_1/8	H080672110
GR-PQ-59-I-1_1/4	H080672104
GR-PQ-59-I-1_3/8	H080672105
GR-PQ-59-I-1_1/2	H080672106
GR-PQ-59-I-1_5/8	H080672111
GR-PQ-59-I-1_3/4	H080672107
GR-PQ-59-I-1_7/8	H080672112
GR-PQ-59-I-2	H080672108
GR-PUR 12/5	H088000606
GR-PUR 25/5	H088000605
GR-PUR 28/5	H088000604

Available versions	Length	Width	Height	Weight	Belt Width
GR-PQ-59-M-006	120 mm (4.724 inch)	25.0 mm (0.984 inch)	8.3 mm (0.327 inch)	0.130 kg (0.3 lb)	
GR-PQ-59-M-008	120 mm (4.724 inch)	25.0 mm (0.984 inch)	8.3 mm (0.327 inch)	0.140 kg (0.3 lb)	
GR-PQ-59-M-010	120 mm (4.724 inch)	35.0 mm (1.378 inch)	8.3 mm (0.327 inch)	0.140 kg (0.3 lb)	
GR-PQ-59-M-011	120 mm (4.724 inch)	35.0 mm (1.378 inch)	8.3 mm (0.327 inch)	0.140 kg (0.3 lb)	
GR-PQ-59-M-012	120 mm (4.724 inch)	35.0 mm (1.378 inch)	8.3 mm (0.327 inch)	0.140 kg (0.3 lb)	
GR-PQ-59-M-013	120 mm (4.724 inch)	35.0 mm (1.378 inch)	8.3 mm (0.327 inch)	0.140 kg (0.3 lb)	
GR-PQ-59-M-014	120 mm (4.724 inch)	35.0 mm (1.378 inch)	8.3 mm (0.327 inch)	0.150 kg (0.3 lb)	
GR-PQ-59-M-015	120 mm (4.724 inch)	35.0 mm (1.378 inch)	8.3 mm (0.327 inch)	0.160 kg (0.4 lb)	
GR-PQ-59-M-016	120 mm (4.724 inch)	35.0 mm (1.378 inch)	8.3 mm (0.327 inch)	0.160 kg (0.4 lb)	

	<i>inch)</i>	<i>)</i>	<i>)</i>	<i>)</i>
GR-PQ-59-M-018	120 mm (4.724 <i>inch)</i>	35.0 mm (1.378 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.170 kg (0.4 <i>lb)</i>
GR-PQ-59-M-020	120 mm (4.724 <i>inch)</i>	50.0 mm (1.969 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.170 kg (0.4 <i>lb)</i>
GR-PQ-59-M-022	120 mm (4.724 <i>inch)</i>	50.0 mm (1.969 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.170 kg (0.4 <i>lb)</i>
GR-PQ-59-M-025	120 mm (4.724 <i>inch)</i>	50.0 mm (1.969 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.170 kg (0.4 <i>lb)</i>
GR-PQ-59-M-030	120 mm (4.724 <i>inch)</i>	50.0 mm (1.969 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.170 kg (0.4 <i>lb)</i>
GR-PQ-59-M-035	120 mm (4.724 <i>inch)</i>	70.0 mm (2.756 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.170 kg (0.4 <i>lb)</i>
GR-PQ-59-M-040	120 mm (4.724 <i>inch)</i>	70.0 mm (2.756 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.200 kg (0.4 <i>lb)</i>
GR-PQ-59-M-050	120 mm (4.724 <i>inch)</i>	70.0 mm (2.756 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.210 kg (0.5 <i>lb)</i>
GR-PQ-59-I-3/8	120 mm (4.724 <i>inch)</i>	35.0 mm (1.378 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.140 kg (0.3 <i>lb)</i>
GR-PQ-59-I-1/2	120 mm (4.724 <i>inch)</i>	35.0 mm (1.378 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.140 kg (0.3 <i>lb)</i>
GR-PQ-59-I-5/8	120 mm (4.724 <i>inch)</i>	35.0 mm (1.378 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.140 kg (0.3 <i>lb)</i>
GR-PQ-59-I-3/4	120 mm (4.724 <i>inch)</i>	50.0 mm (1.969 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.170 kg (0.4 <i>lb)</i>
GR-PQ-59-I-7/8	120 mm (4.724 <i>inch)</i>	50.0 mm (1.969 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.170 kg (0.4 <i>lb)</i>
GR-PQ-59-I-1	120 mm (4.724 <i>inch)</i>	50.0 mm (1.969 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.170 kg (0.4 <i>lb)</i>
GR-PQ-59-I-1_1/8	120 mm (4.724 <i>inch)</i>	50.0 mm (1.969 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.160 kg (0.4 <i>lb)</i>
GR-PQ-59-I-1_1/4	120 mm (4.724 <i>inch)</i>	50.0 mm (1.969 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.170 kg (0.4 <i>lb)</i>
GR-PQ-59-I-1_3/8	120 mm (4.724 <i>inch)</i>	70.0 mm (2.756 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.200 kg (0.4 <i>lb)</i>
GR-PQ-59-I-1_1/2	120 mm (4.724 <i>inch)</i>	50.0 mm (1.969 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.170 kg (0.4 <i>lb)</i>
GR-PQ-59-I-1_5/8	120 mm (4.724 <i>inch)</i>	70.0 mm (2.756 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.200 kg (0.4 <i>lb)</i>
GR-PQ-59-I-1_3/4	120 mm (4.724 <i>inch)</i>	70.0 mm (2.756 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.200 kg (0.4 <i>lb)</i>
GR-PQ-59-I-1_7/8	120 mm (4.724 <i>inch)</i>	70.0 mm (2.756 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.200 kg (0.4 <i>lb)</i>
GR-PQ-59-I-2	120 mm (4.724 <i>inch)</i>	70.0 mm (2.756 <i>inch)</i>	8.3 mm (0.327 <i>inch)</i>	0.200 kg (0.4 <i>lb)</i>
GR-PUR 12/5	250 mm (9.843 <i>inch)</i>	128.0 mm (5.039 <i>inch)</i>	39.9 mm (1.571 <i>inch)</i>	kg (<i>lb</i>)
GR-PUR 25/5	250 mm (9.843 <i>inch)</i>	128.0 mm (5.039 <i>inch)</i>	39.9 mm (1.571 <i>inch)</i>	kg (<i>lb</i>)
GR-PUR 28/5	250 mm (9.843 <i>inch)</i>	128.0 mm (5.039 <i>inch)</i>	39.9 mm (1.571 <i>inch)</i>	kg (<i>lb</i>)

Disclaimer

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.