

PM-609/160W Hot-pressing device

The PM-609/160W is a lightweight hot-pressing device designed for Flexproof and Thermofix joining of Habasit belts up to a width of 600 mm and a thickness of 10 mm. Thanks to a 160 mm wide heat equalization plate, the press can be used also for 10/120 Flexproof geometry.



Adjustable Temperature	Adjustable by control unit		
Cooling Media	Water (ext. supply)		
Max Belt Thickness	10 mm		0.39 inch
Belt/tape width max. for joining angle of 60°	435 mm		
Belt/tape width max. For joining angle of 75°	535 mm		
Belt/tape width max.	600 mm		24 inch
Pneumatics Operating Pressure	3 bar		
Custom Tariff	85158090		

Fabrication Tools

PM-609/160W



Available versions	Item number	Power supply	Control unit	Cooling unit
PM-609/160W-M-APM/4	H088000275	3ph 230V 60Hz	PMR-08	PMC-04M
PM-609/160W-M-APM/5	H088000276	3ph 400V 50Hz	PMR-08	PMC-04M
PM-609/160W-M-APM/8	H088000277	1ph 230V 50Hz	PMR-08	PMC-04M
PM-609/160W-M-CPM/4	H088000269	3ph 230V 60Hz	PMR-07	PMC-04M
PM-609/160W-M-CPM/5	H088000270	3ph 400V 50Hz	PMR-07	PMC-04M
PM-609/160W-M-CPM/8	H088000271	1ph 230V 50Hz	PMR-07	PMC-04M
PM-609/160W-S-AAX/4	H088000272	3ph 230V 60Hz	PMR-08	PMC-06
PM-609/160W-S-AAX/5	H088000273	3ph 400V 50Hz	PMR-08	PMC-06
PM-609/160W-S-AAX/8	H088000274	1ph 230V 50Hz	PMR-08	PMC-06
PM-609/160W-S-CCX/4	H088000266	3ph 230V 60Hz	PMR-07	PMC-07
PM-609/160W-S-CCX/5	H088000267	3ph 400V 50Hz	PMR-07	PMC-07
PM-609/160W-S-CCX/8	H088000268	1ph 230V 50Hz	PMR-07	PMC-07

Available versions	Length	Width	Height	Weight	Operating temperature max
PM-609/160W-M-APM/4	925 mm (36.417 inch)	380.0 mm (14.961 inch)	300.0 mm (11.811 inch)	46 kg (101.4 lb)	200 °C ()
PM-609/160W-M-APM/5	925 mm (36.417 inch)	380.0 mm (14.961 inch)	300.0 mm (11.811 inch)	46 kg (101.4 lb)	200 °C ()
PM-609/160W-M-APM/8	925 mm (36.417 inch)	380.0 mm (14.961 inch)	300.0 mm (11.811 inch)	46 kg (101.4 lb)	200 °C ()
PM-609/160W-M-CPM/4	925 mm (36.417 inch)	380.0 mm (14.961 inch)	300.0 mm (11.811 inch)	46 kg (101.4 lb)	200 °C ()
PM-609/160W-M-CPM/5	925 mm (36.417 inch)	380.0 mm (14.961 inch)	300.0 mm (11.811 inch)	46 kg (101.4 lb)	200 °C ()
PM-609/160W-M-CPM/8	925 mm (36.417 inch)	380.0 mm (14.961 inch)	300.0 mm (11.811 inch)	46 kg (101.4 lb)	200 °C ()
PM-609/160W-S-AAX/4	925 mm (36.417 inch)	380.0 mm (14.961 inch)	300.0 mm (11.811 inch)	46 kg (101.4 lb)	200 °C ()
PM-609/160W-S-AAX/5	925 mm (36.417 inch)	380.0 mm (14.961 inch)	300.0 mm (11.811 inch)	46 kg (101.4 lb)	200 °C ()
PM-609/160W-S-AAX/8	925 mm (36.417 inch)	380.0 mm (14.961 inch)	300.0 mm (11.811 inch)	46 kg (101.4 lb)	200 °C ()
PM-609/160W-S-CCX/4	925 mm (36.417 inch)	380.0 mm (14.961 inch)	300.0 mm (11.811 inch)	46 kg (101.4 lb)	200 °C ()
PM-609/160W-S-CCX/5	925 mm (36.417 inch)	380.0 mm (14.961 inch)	300.0 mm (11.811 inch)	46 kg (101.4 lb)	200 °C ()
PM-609/160W-S-CCX/8	925 mm (36.417 inch)	380.0 mm (14.961 inch)	300.0 mm (11.811 inch)	46 kg (101.4 lb)	200 °C ()

Disclaimer

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice. EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.