

# Seamless Belts

## E3637ZG



### Main industry segments

Cardboard box manufacturing

### Applications

Folder-gluer belt

### Special features

Abrasion resistant, Abrasion resistant on both sides

Product Construction / Design	
Pulley side material	Habidur (Rubber)
Pulley side surface	Fine structure
Pulley side color	Black
Traction layer (material)	Polyester (PET)
Conveying side material	Natural rubber (NR)
Conveying side surface	Buffed finish
Conveying side color	Tan

Product characteristics	
Product Modulus Type	
Carrying rollers suitable	
Antistatically equipped	Yes
Food suitability, FDA conformance	Yes - acc. to 21CFR parts 170 - 199. Contact your Habasit representative for detailed information.

Technical data	
Static coefficient of friction (conveying side / copier paper) (reference - cover)	2.60
Dynamic coefficient of friction (conveying side / copier paper) (reference - cover)	2.40 -
Coefficient of friction (running side / steel driving pulley)	0.60 -
Seamless manufacturing width	305 mm <span style="float: right;">12 inch</span>

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554).

# Seamless Belts

## E3637ZG



### Chemical resistance

Link to 'Chemical resistance information': <http://www.habasit.com/en/chemical-resistance.htm>

### Mode of use or conveyance

### Calculations

For most applications calculation is not required. Should you still need a calculation: please ask Habasit.

### Recommendation

Protect belts from sunlight/UV-radiation/dust and dirt. Store spare belts in a cool and dry place and if possible in their original packaging.

Group	Traditional Seamless Belts
Sub-Group	Rubber Cover
Item number	Tag not found: Tag: Item_No; Product: 6793
Customs tariff number	Tag not found: Tag: CTariff_No; Product: 6793

### Disclaimer

#### Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice. EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.