

HabaSYNC® Timing Belts Covers

Foam rubber smooth



Product Construction / Design	
Material	Natural rubber (NR)

Technical data		
Min. operating temperature admissible (continuous)	-20 °C	-4 °F
Max. operating temperature admissible (continuous)	65 °C	149 °F

Product code	Thickness		Color	Conveying side surface	Conveying side property	Thickness factor	Food grade ¹	Density of cover:	
	mm	inch						g/cm ³	lb/ft ³
AC-FORUB-6-FB46	6.0	0.24	Orange	Open-cell structure	Medium-adhesive	10	-	0.20	0.003
AC-FORUB-8-FB46	8.0	0.31	Orange	Open-cell structure	Medium-adhesive	10	-	0.20	0.003
AC-FORUB-10-FB46	10.0	0.39	Orange	Open-cell structure	Medium-adhesive	10	-	0.20	0.003
AC-FORUB-12-FB46	12.0	0.47	Orange	Open-cell structure	Medium-adhesive	10	-	0.20	0.003
AC-FORUB-15-FB46	15.0	0.59	Orange	Open-cell structure	Medium-adhesive	10	-	0.20	0.003
AC-FORUB-20-FB46	20.0	0.79	Orange	Open-cell structure	Medium-adhesive	10	-	0.20	0.003
AC-FORUB-28-FB75	28.0	1.10	Orange	Open-cell structure	Medium-adhesive	10	-	0.20	0.003
AC-FORUB-30-FB52	30.0	1.18	Orange	Open-cell structure	Medium-adhesive	10	-	0.20	0.003

Hardness and *Thickness* are statistical values which may vary slightly in between different production lots.

Recommended minimum pulley diameter is the result of multiplying the cover *Thickness* by the *Thickness factor*. For design purposes, always use the larger suggested diameter of the belt and cover selected. Limited representative testing based on a standard configuration is carried out to estimate minimum pulley diameters. Please contact Habasit for specific guidance regarding non-standard applications, including, but not exclusively, when profiles or cleats are used.

All covers may not be available in your local market. Please consult your local Habasit representative.

All data are approximate values under standard climatic conditions: 23°C/73°F, 50% relative humidity (DIN 50005/ISO 554).

HabaSYNC® Timing Belts Covers

Foam rubber smooth



Chemical resistance

Link to 'Chemical resistance information': <https://rims.habasit.com>

Group	HabaSYNC® Timing Belts Covers
Sub-Group	Foam Covers

Disclaimer

Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.