



**Standard materials:** PE10 green Ultra High Molecular Weight Polyethylene.

**Standard length:** 3.0 m bar.

**Application:** Used as a sliding support in conveying and linear movement applications for HabaSYNC® timing belts. With its good wear and chemical resistance, and inherent low noise properties, it works well with all types of machinery. This is used in a wide range of industries such as bottling, packaging, materials handling, and food processing.

Code	Belt types	B	H	b	h
		mm	mm	mm	mm
SF-02-PE10G-003+RC	T5 16-AT5 16	25.0	10.0	17.0	1.8
SF-03-PE10G-003+RC	T5 25-AT5 25	34.0	10.0	26.0	1.8
SF-04-PE10G-003+RC	T5 32-AT5 32	41.0	10.0	33.0	1.8
SF-05-PE10G-003+RC	T5 50-AT5 50	59.0	10.0	51.0	1.8
SF-08-PE10G-003+RC	T10 16-AT10 16	25.0	15.0	17.0	3.8
SF-09-PE10G-003+RC	T10 25-AT10 25	34.0	15.0	26.0	3.8
SF-10-PE10G-003+RC	T10 32-AT10 32	41.0	15.0	33.0	3.8
SF-11-PE10G-003+RC	T10 50-AT10 50	59.0	15.0	51.0	3.8
SF-12-PE10G-003+RC	T10 75-AT10 75	84.0	15.0	76.0	3.8
SF-13-PE10G-003+RC	T10 100-AT10 100	109.0	15.0	101.0	3.8
SF-16-PE10G-003+RC	T20 25-AT20 25	34.0	20.0	26.0	7.0
SF-17-PE10G-003+RC	T20 32-AT20 32	41.0	20.0	33.0	7.0
SF-18-PE10G-003+RC	T20 50-AT20 50	59.0	20.0	51.0	7.0
SF-19-PE10G-003+RC	T20 75-AT20 75	84.0	20.0	76.0	7.0
SF-20-PE10G-003+RC	T20 100-AT20 100	109.0	20.0	101.0	7.0

**Note:** All data are approximate values under standard climatic conditions: 23 °C / 73 °F, 50% relative humidity (according to DIN 50005 / ISO 554).



### **Disclaimer**

#### **Product Application Disclaimer (valid for ALL Habasit products and mentioned on all PDS)**

This disclaimer is made by and on behalf of Habasit and its affiliated companies, directors, employees, agents and contractors (hereinafter collectively "HABASIT") with respect to the products referred to herein (the "Products"). SAFETY WARNINGS SHOULD BE READ CAREFULLY AND ANY RECOMMENDED SAFETY PRECAUTIONS BE FOLLOWED STRICTLY! Please refer to the Safety Warnings herein, in the Habasit catalogue as well as installation and operating manuals. All indications / information as to the application, use and performance of the Products are recommendations provided with due diligence and care, but no representations or warranties of any kind are made as to their completeness, accuracy or suitability for a particular purpose. The data provided herein are based on laboratory application with small-scale test equipment, running at standard conditions, and do not necessarily match product performance in industrial use. New knowledge and experience may lead to re-assessments and modifications within a short period of time and without prior notice.

EXCEPT AS EXPLICITLY WARRANTED BY HABASIT, WHICH WARRANTIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, THE PRODUCTS ARE PROVIDED "AS IS". HABASIT DISCLAIMS ALL OTHER WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT, OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE, ALL OF WHICH ARE HEREBY EXCLUDED TO THE EXTENT ALLOWED BY APPLICABLE LAW. BECAUSE CONDITIONS OF USE IN INDUSTRIAL APPLICATION ARE OUTSIDE OF HABASIT'S CONTROL, HABASIT DOES NOT ASSUME ANY LIABILITY CONCERNING THE SUITABILITY AND PROCESS ABILITY OF THE PRODUCTS, INCLUDING INDICATIONS ON PROCESS RESULTS AND OUTPUT.